

[54] **PUSHBUTTON SWITCH WITH COIL SPRING CONTACT**

[75] Inventors: **Yukio Kashio**, Tokyo; **Hiroshi Ishii**, Sagamiko-machi, both of Japan

[73] Assignee: **Casio Computer Co., Ltd.**, Tokyo, Japan

[22] Filed: **Sept. 6, 1972**

[21] Appl. No.: **286,843**

[30] **Foreign Application Priority Data**

Mar. 9, 1972 Japan..... 47-23607

[52] U.S. Cl..... **200/276**, 200/159 R, 200/292

[51] Int. Cl..... **H01h 1/06**, H01h 13/52

[58] Field of Search..... 200/159 R, 159 A, 166 BA, 200/166 PC, 166 BH, 276, 292

[56] **References Cited**

UNITED STATES PATENTS

2,444,552	7/1948	Brantingson.....	200/166 BA X
2,734,104	2/1956	Gollhofer.....	200/276 X
3,379,851	4/1968	Weremy.....	200/276 X

3,679,853 7/1972 Holzer 200/166 PC X

FOREIGN PATENTS OR APPLICATIONS

560,809	6/1929	Germany.....	200/166 BA
872,778	6/1942	France.....	200/166 BA

Primary Examiner—Robert K. Schaefer

Assistant Examiner—William J. Smith

Attorney, Agent, or Firm—Flynn & Frishauf

[57]

ABSTRACT

A switching device comprising a first electrode mounted on the plain surface of an insulation plate and a second electrode formed on said plain surface of said insulation plate at a sufficient spacing from the first electrode to be insulated from said first electrode and with a different diameter from that of said first electrode. The electric connection of both electrodes is effected by keeping one end of a coil spring connected to either of said electrodes and compressing the other end of the coil spring upon depression of an actuator, so as to connect said other end of the coil spring to the other of the electrodes.

18 Claims, 3 Drawing Figures

